

## Clifton Cameras Product Specification

### Profoto Connect Pro Full Spec

<b>Product numbers</b>	
Profoto Connect Pro (Non-TTL)	901320
Profoto Connect Pro (Canon)	901321
Profoto Connect Pro (Nikon)	901322
Profoto Connect Pro (Sony)	901323 (Not available until further notice)
Profoto Connect Pro (Fujifilm)	901324
Profoto Connect Pro (Leica)	901325
<b>Compatibility</b>	
Profoto Connect Pro (Non-TTL)	Any camera with a ISO hotshoe mount
Profoto Connect Pro (Other brand versions)	Camera models listed on <a href="http://www.profoto.com">www.profoto.com</a>
<b>Wireless Connectivity</b>	
Built-in connectivity	AirX
Frequency bands	2.4 GHz
Supported Profoto Air functions (Non-TTL)	Sync, Remote control (Air 1 and Air 2)
Supported Profoto Air functions (Other versions)	Sync, TTL, HSS, Remote control (Air 1 and Air 2)
No of Air channels	100 (1-100)
No of remote-control groups per Air channel	6 (A-F).
Supported apps for Bluetooth devices	Profoto Control apps
Operating range	Flash triggering and remote control up to 300 m (1000 ft). TTL and HSS up to 100 m (330 ft).
<b>Connectors</b>	
Sync	Hotshoe
<b>Powering</b>	
Power supply	3 x AAA (Lithium, Alkaline or NiMH)
Battery capacity	Up to 50 hours
<b>Measurements</b>	
Width	51 mm (2.01 in)
Length	90 mm (3.54")
Height	40 mm (1.58 in)
Weight	90 g / 0.20 lb without batteries 125 g / 0.28 lb with batteries