



Clifton Cameras Product Specification

Canon RF 70-200mm F4L IS USM Full Spec

OPTICAL FEATURES/SPECIFICATIONS

Image size - Full Frame
Angle of view - 29° - 10°
(horzntl, vertl, diagnl) - 19° 30' - 7°, 34° - 12°
Lens construction (elements/groups) - 16 / 11
No. of diaphragm blades - 9
Minimum aperture - 32
Closest focusing distance (m) - 0.6
Maximum magnification (x) - 0.28
Distance Information - Yes
Image stabilizer [2] - 5
AF actuator - Dual NANO USM

PHYSICAL SPECIFICATIONS

Dust/moisture resistance [1] - Yes
Filter diameter (mm) - 77
Max. diameter x length (mm) - 83.5 x 11 [3]
Weight (g) - 695³

ACCESSORIES

Lens Cap - E-77II
Lens hood - ET-83G (WIII)
Lens case/pouch - LP1319
Rear End Cap - Lens Dust Cap RF
Extender Compatibility - Not compatible
Other Accessories

Footnotes

[1] Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

[2] Tested under CIPA standards

[3] Lens dimensions when in retracted state