

Clifton Cameras Product Specification

Canon Speedlite Transmitter ST-E3-RT (Ver.3) Full Spec

Specifications in detail

Flash Modes

- Auto Exposure Control

E-TTL II / E-TTL

- High Speed Sync (FP)

Yes

- Manual / Output Settings

Yes - 1/1- 1/128

- Manual Steps

1/3 step

- Strobe / Output Settings

Yes - 1/4-1/128

- Stroboscopic Frequency

1-500Hz

Flash-Related Function

- FE Lock

Yes

- FE Memory

No

- Flash Exposure Compensation

Yes

- Flash Exposure Bracketing

Yes

- Second-Curtain Flash Sync

No

- Modelling Flash

Yes

Wireless Flash

- Transmitter

Yes

- Transmission Type

Radio

- Transmitter Range

Indoors: 30m

Outdoors: 30m

- Receiver

No

- Number of Groups

5 - A,B,C,D or E

- Number of Channels

15

- Remote Shutter Release

Yes

AF Assist

- AF-Assist Beam

No

- Number of AF Points Supported

-



- AF-Assist Beam Type

-

Power Source

- Battery

2 x AA batteries

- Minimum Recycling Time

N/A

- External Power Supply

No

Construction

- Dust and Water Resistance

Yes

- Mounting Foot Material

Metal

Miscellaneous

- Custom Function

8 (3 personal functions)

- Flash Settings from Camera Menu

Yes

- External Flash Exposure Sensor

No

- PC Terminal

No

- Accessories (Included)

Soft case

- Accessories (Optional)



Off-Camera Shoe Cord OC-E3, Release Cable SR-N3

- Compatible Speedlites

EL-1, 600EX II-RT, 600EX-RT, 430EX III-RT

Physical Specifications

- Dimensions (W x H x D)

67.4 x 61.5 x 77.4

- Weight

110g