

Clifton Cameras Product Specification

Elinchrom THREE Off Camera Flash Dual Kit Full Spec

Size (Single Head):	25.3 x 16.5 x 10.5 cm
Type:	TTL Battery Flash Kit
Weight (Single Head):	1650 g
Power Ws:	261 Ws
Power Range:	7-261 Ws
Power Range (f stops):	6
Flash mode:	Manual / TTL / HSS (with Transmitter Pro)
Recycling time s:	0.08-1.2
Colour Temp °K:	5900 K Action / 5600 K HSS (± 150 K)
Best Flash Duration:	Action: 1/8500s / Normal: 1/1550s (T0.1)
Flashes from one charge at min. Power:	LED Lamp Off: 11250 / LED Lamp on 100%: 9000
Flashes from one charge at max. Power:	LED Lamp Off: 525 / LED Lamp on 100%: 400
Power Source:	Lithium-Ion Built-in - 41.04Wh
Voltage Stabilisation:	Yes, +/- 0.5%
Modelling Light:	Dimmable 20w (120w equivalent) Bi-Colour LED, CRI 95, 3000 Lumen
Triggering:	Built-In Skyport (20 frequency channels, 4 Groups), Built-In Bluetooth
Auto Power Dumping:	Adjusts power settings automatically in real time
Fan Cooled:	Smart proactive cooling
Input:	USB-C
Battery Charge Status:	On the display if ON and side logo if OFF
Charging Time (with 65W USB-C Wall Charger):	60m. (80%) – 100m. (100%) in Fast charge / 80m. (80%) – 135m. (100%) in Slow charge
Charging Time (with 18W 20000 mAh Power Bank):	80m. (80%) – 135m. (100%) in Fast charge / 105m. (80%) – 180m. (100%) in Slow charge
LED run time (LED only, min/max power):	10 hours / 90 minutes
Umbrella fitting (on tilt head):	7 – 8 mm