

# Clifton Cameras Product Specification

## Godox X3 Transmitter Full Spec

### Compatible Cameras

X3-C – Canon EOS cameras (E-TTLII auto flash)

X3-N - Nikon cameras (i-TTL auto flash)

X3-S – Sony cameras (TTL auto flash)

X3-F – Fujifilm cameras (TTL auto flash)

X3-O – OM System cameras (TTL auto flash)

Built-in Lithium Battery	3.7V $\approx$ 850mAh
Charging Time	$\approx$ 2h
Standby Time	$\approx$ 7 days
TTL Auto Flash	√
Manual Flash	√
Multi Flash	√
High Speed Sync	√
Front Curtain Sync	√
Rear Curtain Sync	√
Flash Exposure Compensation	+3EV (exposure value) , adjustable in 1/3 EV increments
Modeling Lamp Flash	Control the modeling lamp by flash trigger
Buzz	Control the buzz by flash trigger



ZOOM Setting	AUTO/Focus length 24-200mm
TCM Transform	Transform the TTL shooting value into the output value
Firmware Upgrade	Upgrade through the USB-C port
Memory Function	Settings will be stored 2 seconds after last operation
Display Panel	Touch screen with adjustable brightness
Transmission Range (approx.)	0-100m
Built-in Wireless	2.4GHz
Channel	32
Wireless ID	OFF/01-99
Group	A-F, 0-9
Dimension	1.61"*1.85"x1.54"
Net Weight≈	48g