



Clifton Cameras Product Specification

Canon Selphy Square QX10 Printer

Printing System

Method

Dye-sublimation thermal transfer printing system

Maximum resolution

287 x 287 dpi

Colours

3 colour inks (yellow, cyan, magenta) with protective over coating
256 levels per colour (24 bit colour depth)

Media & Cartridge

Sticker paper

72 x 85 mm, 68 x 68 mm printable area

Ink Cartridge

Included with media

Image Longevity

100 Years Print ¹

Print Speeds

Sticker paper

approx. 43 sec ²

Printing

Print Modes & Settings

Controlled by SELPHY Photo Layout app

Print Method

Direct From a Smart Device

Compatible iOS and Android devices via Direct Wi-Fi, using app SELPHY Photo Layout

Power Source

AC Power Supply

Not supported

Battery Pack

Built-in, 20 sheet maximum print capacity per full charge

Power Consumption

3W or less (standby), 62W or less (printing)



Accessories

Media

Color Ink / Label Set XS-20L

Other

USB Micro B connector to USB Type-A connector for charging (included)

All data is based on Canon's standard testing methods.

Subject to change without notice.

1. To test the image permanence of prints that are stored in an album, we use an accelerated testing method similar to how the image permanence of silver-halide photo papers are measured when stored in dark places. Print samples are printed with the optical density of 1.0 (each Bk, C, M,Y). The samples are kept in a certain environment of high temperature and 50% humidity. The rate of the decrease in the optical density and rate of yellow discoloration are recorded. The recorded results are then converted to the length of time when print image is kept in an environment of 23°C/ 50% humidity. <Criteria for estimation of print longevity> 'The point where monochromatic/ reflective optical density shows loss of 30% (starting density of 1.0).
2. Print speed can vary dependent on data size, print method, and print finish setting. Print speed is measured from start of printing excluding paper handling