



Clifton Cameras Product Specification

Canon RF 800mm f5.6L IS USM Lens Full Spec

OPTICAL FEATURES / SPECIFICATIONS	
Image size	Full Frame
Angle of View (Horzntl, Vertl, Diagnl)	02°35', 01°40', 03°05'
Lens Construction (elements/groups)	26/18
Special Optics	2x Fluorite, 1X SUD, 1x UD
No. of diaphragm blades	9
Minimum Aperture	64
Closest Focusing Distance (m)	2.6
Maximum Magnification (x)	0.34
Control Ring	via Focus ring
Image Stabilizer OIS1	4
Image Stabilizer IBIS x OIS1	4.5
AF Actuator	Ring USM
Coatings	ASC, Super Spectra
Fluorine	Front
PHYSICAL SPECIFICATIONS	
Dust/Moisture Resistance ²	Yes
Exterior Coating	Heat Shield
Filter Diameter (mm)	52
Max. Diameter x Length (mm)	163 x 432
Weight (g)	3140

ACCESSORIES	
Lens Cap	E-180E
Lens Hood	ET-155 (WIII)
Lens case/pouch	Lens Soft Case LS600
Rear cap	Lens Dust Cap RF
Extender Compatibility	Compatible with RF Extender only



Other Accessories	Canon drop-in 52mm filters Canon Drop-In Circular Polarizing Filter 52 (WIII)
SPECIFICATIONS 1.4X EXTENDER	
Focal Length	1120mm
Maximum Aperture	8-91
Maximum Magnification	0.49x
AF Possible	Yes
IS	Yes
SPECIFICATIONS 2X EXTENDER	
Focal Length	1600mm
Maximum Aperture	11-91
Maximum Magnification	0.71x
AF Possible	Yes
IS	Yes