



OM SYSTEM OM-1 Mark II Specification

[OM SYSTEM OM-1 Mark II](#)

Sensor Effective Resolution/Type: 20.4 Megapixel 4/3 Stacked BSI Live MOS

Dust Reduction: Super Sonic Wave Filter

Processor: TruePic™ X Dual Quad Core Processor

Image Stabilization System: 5-Axis Image Stabilization with up to 8.5 Shutter Speed Steps Compensation

Viewfinder: Eye-level OLED electronic viewfinder, approx. 5.76M dots

Rear Monitor: 3.0-inch vari-angle monitor (electrostatic capacitance touch panel), Approx. 1.62M dots (3:2)

Weatherproofing: Dust, Splash and Freezeproof (IP53 Rated)

Focusing System: High-speed imager AF: Imager phase detection AF and imager contrast AF used in combination

Number Of Blades: 7 (circular aperture diaphragm)

Focusing Points:

Cross-type phase detection AF (1,053 points)

Contrast AF (1,053 points) / All target

Single target (1 point), Small target (9 points), Cross target (39 points)

Middle target (63 points), Large target (165 points)

Custom target* (AF area and its increment steps selectable)

AI Detection AF: Human, Formula cars, rally cars, motorcycles / Aircrafts, helicopters / Bullet trains, standard trains, steam locomotives / Birds / Dogs, cats

Sequential Shooting:

[Sequential shooting] approx 10 fps with selectable 1-10 fps

[Anti-shock sequential shooting] approx 10 fps with selectable 1-10 fps

[Silent sequential shooting] approx 20 fps with selectable 5, 10, 15, 20 fps without blackout

[Silent sequential shooting SH1] approx 120 fps with selectable 60, 100, 120 fps without blackout

*Slower shutter speeds and flash can not be used.

[Silent sequential shooting SH2] approx 50 fps with selectable 12.5, 16.7, 25, 50fps without blackout

*Compatible lenses are limited.

[Pro Capture] approx 20 fps with selectable 5, 10, 15, 20 fps

*When in Pro Capture mode, slower shutter speeds and flash can not be used

[Pro Capture SH1] approx 120 fps with selectable 60, 100, 120 fps

*When in Pro Capture mode, slower shutter speeds and flash can not be used

[Pro Capture SH2] approx 50 fps with selectable 12.5, 16.7, 25, 50 fps

*Slower shutter speeds and flash can not be used.

*Compatible lenses are limited.

Additional Features:

Focus Stacking

Art Filters

Live Composite

Exposure Bracketing

Live ND

Live GND

4K Video Recording

Wireless Shooting & GPS Info via Smartphone

Vertical Video

High Res Mode

Weight: Approx. 511 g (body only)

Dimensions: Approx. 134.8 mm (W) × 91.6 mm (H) × 72.7 mm (D) *Based on CIPA standards: excludes protrusions

Box Contents:

Body, CB-USB13 USB cable, CC-1 Cable clip, CP-2 Cable protector, Shoulder strap,

Instruction manual, Warranty card, BLX-1 Li-ion battery.