

Clifton Cameras Product Specification

Insta360 Flow - Standard

Specifications

Weight: Gimbal: Approx. 369g (13oz)

Magnetic Phone Clamp: Approx. 32g (1.1oz)

Dimensions(D*W*H) * Not incl. phone clamp: Folded: 79.6x162.1x36mm (3.1x6.4x1.4in)

Unfolded: 73.6x269.4x69.9mm (2.9x10.6x2.8in)

Compatible Phone Thickness: 6.9-10mm (0.3-0.4in)

Compatible Phone Width: 64-84mm (2.5-3.3in)

Compatible Phone Weight: 130-300g (4.6-10.6oz)

Port: USB-C

Built-In Selfie Stick Length: 215mm (8.5in)

Built-In Tripod Dimensions: Extended Length: 80mm (3.1in)

Extended Diameter: 187.6mm (7.4in)

Battery Capacity: 2900mAh

Run Time: 12 hours

*Tested under room temperature conditions (25°C/77°F), with the

gimbal fully balanced and placed on a flat surface.

Charging Time: 2 hours (5V/2A)

Charging Temperature: 0°C to 40°C (32°F to 104°F)

Operating Temperature: $-10^{\circ}\text{C} \text{ to } 40^{\circ}\text{C} \text{ (}14^{\circ}\text{F to } 104^{\circ}\text{F)}$

Mechanical Range: Pan: -230° to 100° / Roll: -150° to 180° / Tilt: -100° to 82°

Max Control Speed: 120°/s

Operating Temperature: -10°C to 40°C (14°F to 104°F)

Mechanical Range: Pan: -230° to 100° / Roll: -150° to 180° / Tilt: -100° to 82°

Max Control Speed: 120°/s

Bluetooth: Bluetooth 5.0