



Clifton Cameras Product Specification

Nikon NIKKOR Z DX 50-250mm f4.5-6.3 VR Lens Full Spec

Mount	Nikon Z mount	
Focal length	50-250mm	
Maximum aperture	f/4.5-6.3	
Lens construction	16 elements in 12 groups (including 1 ED glass element).	
Angle of view	31°30'-6°30' (DX image area)	
	Internal Focusing (IF) system	
Vibration reduction (lens shift using voice coil motors)	VR	NORMAL: 5.0 stops
	Blur reduction when a tripod is used	Yes
Diaphragm	Automatic electromagnetic aperture control.	
Diaphragm blades	7 (rounded diaphragm opening)	
Aperture range	f/4.5-22 (at 50mm), f/6.3-40 (at 250mm)	
Minimum focus distance	0.5 m/1.64 ft from focal plane (at 50mm; 1.0m/3.29 ft at 250mm)	
Maximum reproduction ratio	0.23x	
Weight	Approx. 405 g/ 14.3 oz	
Dimensions	Approx. 74mm/3 in. x 110 mm/4.4in (when retracted)	
Filter-attachment size	62mm	
Colour	Black	
AF actuator	STM (stepping mode)	
Nano Crystal Coat	No	



ARNEO Coat		No
Focus mode switch		No
Lens cap		LC-62B 62mm snap-on Front Lens cap (supplied)
Rear lens cap	Sold separately	LF-N1 (supplied)
	Sold as a kit	White lens capp JMD00601 (supplied)
Lens hood		HB-90A Bayonet Hood (optional)
Lens case		CL-C1 Lens Case (optional)
Circular Polarizing Filter II	Lens only	Yes
	With hood	Yes
Compatiable accessories		62mm screw-on filters (optional), 62mm Neutral Color NC filter, 62mm Circular Polarizing Filter II, 62mm New Soft Focus Filter.