

# **Clifton Cameras Product Specification**

## Leica Super-Vario-Elmarit-SL 14-24mm f2.8 ASPH Lens Full Spec

### Order No.

Black, anodized - 11194

## View angle (diagonal/horizontal/vertical)

Full-frame (24 x 36 mm) - 14 mm: 112.4°/102.4°/79.3° l 24 mm: 85.0°/74.6°/53.9°

#### Lens system

Number of lenses/assemblies - 18/13 Position of the entrance pupil before the bayonet - 14 mm: 96.2 mm | 24 mm: 91.6 mm Focus range - 14mm: 280mm to  $\infty$  | 24mm: 280mm to  $\infty$ 

#### Focusing

Setting - Choose automatic (Autofocus) or manual mode on the camera Smallest object field - Full-frame: **14 mm:** 273 mm x 410 mm | **24 mm:** 176 mm x 265 mm Largest scale - **14 mm:** 1:11.4 | **24 mm:** 1:7.4

#### Aperture

Setting/Function - Electronically controlled aperture, setting on the camera, half or third values can also be set Smallest aperture – 22

Bayonet - Leica L bayonet fitting with contact strip

Firmware - Lens firmware can be updated via the camera

Coating - Hydrophobe Aqua-Dura® coating on external lenses

Material - Aluminum full-metal housing, black anodized, dust and splash water-protected

Filter thread - Holder for foil filter on bayonet

Lens hood - Permanently mounted

#### Dimensions

Length – Approx. 131 mm Diameter – Approx. 85 mm Weight – Approx. 855 g