



Clifton Cameras Product Specification

Nikon D5600 Body Only Full Spec

Model	D5600
Effective Pixels	24.2 million
Image Sensor	Nikon DX-format CMOS sensor without optical low-pass filter
Image Processing	EXPEED 4 image-processing engine, Picture Control, Active D-Lighting
Viewfinder	Pentamirror type, approx. 95% frame coverage, approx. 0.82× magnification
Monitor	8.1-cm/3.2-in., TFT, approx. 1037k-dot, 170° viewing angle, approx. 100% frame coverage, touch-screen, vari-angle monitor
Touch Fn	Focus point selection, ISO sensitivity (auto sensitivity control [On/Off]), Active D-Lighting setting, HDR, auto bracketing, AF area mode, viewfinder grid display, aperture setting
Shutter Speed	1/4000 to 30 s in steps of 1/3 or 1/2 EV, bulb, time
Continuous Shooting	Approx. 5 fps (in 12-bit RAW), approx. 4 fps (14-bit RAW)
ISO Sensitivity	ISO 100 to 25600
Autofocus	39 points (9 cross-type sensors)
Exposure Metering	2016-pixel RGB sensor
Built-in Flash	Guide number approx: 12/39 (ISO 100, m/ft, 20C/68F)
Scene Modes/Effects	16 options, 10 special effects, 20 image-editing functions
Movie	MOV (Video: H.264/audio: LPCM), 1080: 60p/50p, 1080: 30p/25p/24p, 720: 60p/50p; high quality/normal are selectable; Time-lapse movie
Audio	Built-in stereo microphone, external stereo microphone employed; microphone sensitivity can be set
HDMI	HDMI output supported (HDMI output of 60p/50p movie is unavailable), HDMI connector (Type C) incorporated
Power Source	EN-EL14a Rechargeable Li-ion Battery, MH-24 Battery Charger
Dimensions (W x H x D) /Weight	124 × 97 × 70 mm/4.9 × 3.9 × 2.8 in., approx. 415 g/14.7 oz (Based on CIPA Guideline; approx. 465 g/1 lb 0.4 oz with batteries and SD memory card)
Wireless Functions	Bluetooth, NFC, Wi-Fi (SnapBridge supported)



Storage media/format SD memory card (SDHC/SDXC [UHS-I supported]); 12-bit/14-bit RAW, JPEG, RAW+JPEG

Interface External microphone connector, Micro-USB connector, accessory terminal, HDMI connector (Type C)

Supplied Accessories EN-EL14a Rechargeable Li-on Battery, MH-24 Battery Charger, AN-DC3 Strap, BF-1B Body Cap, DK-25 Rubber Eyecup