

Clifton Cameras Specifications Sheet

For the
Sony Cyber-Shot RX0 II Premium Tiny Tough Camera

Imaging

Pixels 15.3 Megapixel

Sensor 1" (13.2 x 8.9 mm) CMOS

File Formats Still Images: JPEG, RAW
Movies: AVCHD, XAVC S

Max Resolution 15 MP: 4800 x 3200

Aspect Ratio 1:1, 3:2, 4:3, 16:9

Image Stabilization Digital

Color Spaces sRGB, Adobe RGB

Optics

Lens	6 Elements in 6 Groups 6 Aspherical Effective Focal Length: 7.9mm (35 mm Equivalent: 24mm) Aperture: f/4
------	----------------------------------------------------------------------------------------------------------------------

Filter Thread	None
---------------	------

Zoom	Clear Image Zoom: 2x
------	----------------------

Focus Range	Auto: 7.87" to Infinity / 20 cm to Infinity
-------------	---------------------------------------------

Exposure Control	
------------------	--

ISO Sensitivity	Auto, 125 to 12800 (Extended Mode:80 to 12800)
-----------------	------------------------------------------------

Shutter	Type: Electronic Speed: 1/4 to 1/32000 Second
---------	--------------------------------------------------

Exposure Metering	Average, Center-Weighted, Highlight, Multi, Spot
-------------------	--------------------------------------------------

Exposure Modes	Modes: Intelligent Auto, Manual, Memory Recall, Movie, Programmed Auto, Superior Auto Compensation: -3 EV to +3 EV (in 1/3 EV Steps)
----------------	--------------------------------------------------------------------------------------------------------------------------------------------

White Balance

Auto, Cloudy, Color Temperature, Color Temperature Filter, Custom, Daylight, Fluorescent (Cool White), Fluorescent (Day White), Fluorescent (Daylight), Fluorescent (Warm White), Incandescent, Shade, Underwater

Continuous Shooting

Up to 16 fps at 15 MP for up to 129 Exposures (JPEG Format)

Self-Timer

2, 5, 10 Sec

Interval Recording

Yes

Remote Control

VCT-SGR1 Shooting Grip (Optional)

Memory

Built-In Memory

None

Memory Card Type

microSDXC
microSDHC
microSD
Memory Stick Micro (M2)
Memory Stick Micro

Recording

Video Recording	Yes, NTSC/PAL
-----------------	---------------

Resolution	3840 x 2160p: 30 fps, 24 fps 1920 x 1080p: 120 fps, 100 fps, 60 fps, 50 fps 1920 x 1080p: 30 fps, 25 fps, 24 fps 1920 x 1080i: 60 fps, 50 fps 1676 x 942p: 250 fps, 240 fps 1676 x 566p: 500 fps, 480 fps, 250 fps, 240 fps 1136 x 384p: 1000 fps, 960 fps, 500 fps, 480 fps 800 x 270p: 1000 fps, 960 fps
------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Video

Audio Recording	Built-In Mic: With Video Optional External Mic: With Video
-----------------	---------------------------------------------------------------

Viewfinder/Display

Screen	1.5" LCD Tilt (230,400 Pixels)
--------	--------------------------------

Screen Coverage	100%
-----------------	------

Connectivity/System Requirements

Connectivity	3.5mm Microphone, HDMI D (Micro), Multi Interface Terminal
--------------	------------------------------------------------------------

Wi-Fi	Yes Built In
-------	--------------

GPS	No
-----	----

Environmental

Operating Temperature	32 to 104°F / 0 to 40°C
-----------------------	-------------------------

Waterproofing	32.8' / 10.0 m
---------------	----------------

Certifications	FCC
----------------	-----

Power

Battery	1 x NP-BJ1 Rechargeable Lithium-Ion Battery Pack, 3.7 VDC, 700 mAh
---------	-----------------------------------------------------------------------

AC Power Adapter	USB (Included)
------------------	----------------
