



Clifton Cameras Product Specification

Xvive U5T2 Two-pack U5 System Full Spec

WIRELESS TYPE	2.4 GHz ISM
BIT DEPTH/SAMPLE RATE	24-bit / 48 kHz
SWITCHABLE CHANNELS	6 (2400-2483.5 MHz)
SIMULTANEOUS CHANNELS	6
FREQUENCY RESPONSE	20 Hz – 20 kHz
DYNAMIC RANGE	Mic: 99 dB; Line: 107 dB
SIGNAL-TO-NOISE RATIO	Mic: 95 dB; Line: 107 dB
TOTAL HARMONIC DISTORTION	0.2%
LATENCY	6 ms
OPERATING RANGE	100 ft
TRANSMITTER	
INCLUDED	U5T
TYPE	Beltpack
CONNECTOR	Mono 3.5 mm (1/8") TRS input
DIMENSIONS	51 x 34 x 65 mm
WEIGHT	55.2 g without battery
STEREO/MONO	Mono
RECEIVER	



RECEIVER

INCLUDED

U5R

TYPE

DSLR cold shoe mount

CONNECTOR

Stereo 3.5 mm (1/8") TRS output

DIMENSIONS

54 x 44 x 65 mm

WEIGHT

53 g without battery

BATTERY

TYPE

Xvive U5B battery: 3.8V Rechargeable Li-ion, 830mAh

LIFE

5 hrs

CHARGING TIME

2.5 hrs

VOLTAGE

5V 2A

USABLE WHILE CHARGING

Yes

Support