

Clifton Cameras Product Specification

Panasonic Lumix LX100 Mark II Digital Camera Specification

Sensor	4/3-inch (1.33-inch) without Low Pass Filter
Camera Effective Pixels	17 Megapixels (21.7 Megapixels) with Multi-Aspect
Lens	24-75mm F1.7-2.8 LEICA DC VARIO-SUMMILUX
Processor	New Venus Engine
Macro	3 CM
Weight	404g (with SD Card, Battery, Body)
ISO	ISO200-25600 / Extended ISO100
Shutter Speed	1/4,000-60 / Time (Max. 120 sec) / Electronic shutter (1/16,000–1)
Exposure Compensation	±5EV
Focus	Light Speed AF with DFD Technology
Burst Shooting	AFS 11 fps / AFC 6.5 fps
4K Video	30p / 25p (PAL) / 24p
4K Photo	30 fps – Auto Marking/Sequence Composition/ Bulk Saving
Post Focus/Focus Stacking	Yes/Yes
Viewfinder (Approx.)	2,760k-dot equivalent/0.38-inch/0.7x (35mm equivalent)
Rear Monitor (Approx.)	1.240k-dot LCD/3.0/Touch
Manual Control	Aperture ring/ Shutter Speed Dial/ Control Ring / Exposure Compensation Dial
Flash	External (Bundled Accessory)
Wireless	Wi-Fi 2.4 GHz
Battery	DMW-BLG10
Battery Life	340 images (LCD) / 270 images (LVF)



New Photo Style	L. Monochrome / L. Monochrome D
Other	Focus Bracket/ Aperture Bracket
Dimensions	404g (with SD card, Battery, Body)