

Clifton Cameras Product Specification

Canon RF 100-500mm F4.5-7.1L IS USM Lens

OPTICAL FEATURES/SPECIFICATIONS	
Image size	Full Frame
35mm film equivalent focal length (mm)	
Angle of view (horzntl, vertl, diagnl)	20°-4°, 14°-2°45', 24°-5°
Lens construction (elements/groups)	20/14
No. of diaphragm blades	9
Minimum aperture	f/32 @ 100mm / f/54 @ 500mm
Closest focusing distance (m)	0.90 at 100mm / 1.2m at 500mm
Maximum magnification (x)	0.33x
Distance Information	Yes
Image stabilizer ^[15]	5
AF actuator	Dual Nano USM
PHYSICAL SPECIFICATIONS	
Dust/moisture resistance ^[4]	Yes
Filter diameter (mm)	77
Max. diameter x length (mm)	93.8 x 207.6 ₁₃
Weight (g)	1530

ACCESSORIES	
Lens Cap	E-77 II
Lens hood	ET-83F (WIII)
Lens case/pouch	LZ1328
Rear End Cap	Lens Dust Cap RF
Magnification with Extension Tube EF12 II	Not compatible
Magnification with Extension Tube EF25 II	Not compatible



Extender Compatibility	Compatible with RF Extender only ¹⁶
Other Accessories	TRIPOD MOUNT RING F (WIII) (supplied)
SPECIFICATIONS 1.4X EXTENDER	
Focal Length	420mm -700mm
Maximum Aperture	f/8 -f/10
Maximum Magnification	0.46
AF Possible	Yes
IS	Yes
SPECIFICATIONS WITH 2X EXTENDER	
Focal Length	600mm-1000mm
Maximum Aperture	f/11-f/14
Maximum Magnification	0.66
AF Possible	yes
IS	yes