



## Clifton Cameras Product Specification

Canon RF-S 18-45mm F4.5-6.3 IS STM

### Optical Features/ Specifications

Image Size: APS-C

35mm Film Equivalent Focal Length (mm): 29-72mm

Angle of View (Horizontal, vertical, Diagonal): 64° 30' - 28° 20', 45° 30' - 19° 05', 74° 20' - 33° 40'

Lens Construction (Elements/ Groups): 7/7

Special Optics: 2 x PMo Aspherical

Number of Diaphragm: 7

Minimum Aperture: 22@ 18mm/ 32@ 45mm

Closest Focusing Distance (m): 0.2 (18mm) (Manual Focus: 0.15)

0.3 (35mm) (Manual Focus: 0.24)

0.35 (45mm) (Manual Focus: 0.25)

Maximum Magnification (x): 0.14 (18mm) (Manual Focus: 0.25)

0.15 (35mm) (Manual Focus: 0.21)

0.16 (45mm) (Manual Focus: 0.26)

Control Ring: Combined Focusing/ Control

Image Stabilizer OIS: 4

Image Stabilizer IBIS x OIS: 6.5

AF Actuator: STM

Coatings: Super Spectra

Fluorine: No

Accessories

Lens Cap: E-49

Lens Hood: EW-53

Lens Case/Pouch: LP814

Rear End Cap: Lens Dust Cap RF



Magnification with Extension Tube EF12 II: Not Compatible

Magnification with Extension Tube EF25 II: Not Compatible

Extender Compatibility: Not Compatible

Extension Tubes: Not Compatible

Physical Specifications

Dust/Moisture Resistance: No

Exterior Coating: -

Filter Diameter (mm): 49

Max. Diameter x Length (mm): 69 x 44.3

Weight (g): 130