



# Clifton Cameras Product Specification

## Canon Speedlite Transmitter ST-E3-RT Version 2

### Specifications

#### Flash Modes

Auto Exposure Control:	E-TTL II / E-TTL
High Speed Sync (FP):	Yes
Manual / Output Settings:	Yes - 1/1 - 1/128 (1/8192)
Manual Steps:	1/3 step
Strobe / Output Settings:	Yes - 1/4 - 1/128 (1/8192)
Stroboscopic Frequency:	1-500Hz

#### Flash-Related Function

FE Lock:	Yes
FE Memory:	Yes
Flash Exposure Compensation:	Yes
Flash Exposure Bracketing:	Yes
Second-Curtain Flash Sync:	Yes
Modelling Flash:	Yes

#### Wireless Flash

Transmitter:	Yes
Transmission Type:	Radio
Transmitter Range:	Indoors: 30m Outdoors: 30m
Receiver:	No
Number of Groups:	5 - A, B, C, D or E
Number of Channels:	15
Remote Shutter Release:	Yes

#### AF Assist



AF-Assist Beam: No

Number of AF Points Supported: -

AF-Assist Beam Type: -

#### **Power Source**

Battery: 2 x AA batteries

Minimum Recycling Time: N/A

External Power Supply: No

#### **Construction**

Dust and Water Resistance: Yes

Mounting Foot Material: Metal

#### **Miscellaneous**

Custom Function: 8 (4 personal functions)

Flash Settings from Camera Menus: Yes

External Flash Exposure Sensor: No

PC Terminal: No

Accessories (Included): Soft case

Accessories (Optional): Off-Camera Shoe Cord OC-E3, Release Cable SR-N3

Compatible Speedlites: EL-1, 600EX II-RT, 600EX-RT, 430EX III-RT

#### **Physical Specifications**

Dimensions (W x H x D): 67.4 x 61.5 x 77.4

Weight: 110g