Clifton Cameras Product Specification

Canon RF 100mm F2.8L MACRO IS USM Full Spec

OPTICAL FEATURES/SPECIFICATIONS	
Image size	Full Frame
Angle of view (horzntl, vertl, diagnl)	20°, 14°, 24°
Lens construction (elements/groups)	17 / 13
Special optics	-
No. of diaphragm blades	9
Minimum aperture	32
Closest focusing distance (m)	0.26
Maximum magnification (x)	1.4
Distance Information	Yes
Image stabilizer OIS1	5-stops (2-stops at 1.0x magnification, under Canon test standards)
Image stabilizer IBIS x OIS1	8-stops
AF actuator	Dual Nano USM
Coatings	Super Spectra
Fluorine	Front
PHYSICAL SPECIFICATIONS	
Dust/moisture resistance2	Yes
Exterior coating	-
Filter diameter (mm)	67
Max. diameter x length (mm)	81.5 x 148
Weight (g)	730
ACCESSORIES	
Lens cap	E-67 II
Lens hood	ET-73C
Lens case/pouch	LP1222
Rear cap	Lens Dust Cap RF

Extender Compatiblity	Not Compatible
Extension Tubes	None
Other Accessories	MacroliteAdapter 67 (optional), Tripod mount ring E (B) with adapter (optional)