



Clifton Cameras Product Specification

Desview R7 Field Monitor Full Spec

Model:	Desview R7	
Size:	7" LED screen	
Resolution:	Full HD 1920 x 1200	
Color Space:	95% NTSC (Rec.709)	
Pixel:	403PPI	
Display ration:	16:10	
Brightness:	1000cd/m2	
Contrast:	1100:1	
Viewing Angle:	178°(H/V)	
Backlight:	LED	
Input:	HDMI 1.4	
Output:	HDML 1.4	
Audio:	3.5mm Stereo Headphone	
HDMI Input/ Output Support Format:	720*480i&720*480p @ 59.94, 60Hz 720*576i & 720*576p @ 50Hz 1280*720p @ 50, 59.94, 60Hz 1920*1080i @ 50, 59.94, 60Hz 1920*1080PsF @ 24, 25, 29.97, 30Hz 1920*1080psf @ 23.93, 24, 25, 29.97,30,50,59.94,60Hz 3840*2160p @ 24,25,30Hz 4096*2160P @ 24Hz	
	for Canon:	C100, C100II, C200, C300, EOS R, 5D Mark IV, 5D Mark III, 1DX2, 6D2, 80D, 7DII and etc.

Camera compatible:	for Sony:	FS7, FS5, A7RII, A7RIII, A7SR II, A7M2, A7M3 and etc.
	for Nikon:	Z6, Z7, D810, D800, D850, D750, D500, D5, D4 and etc.
	for Panasonic:	EVA1, Lumix GH5S, Lunis GH5, Lumix GH4 and etc.
	for Fujifilm:	X-T3, X-T2, X-T20, X-Pro2 and etc.
	for Blackmagic Design	BMPPC 4K, BMPCC, BMCC and etc.
Monitor Function:	<p>Volume meter; Safe area; Load 3D LUTs; Aspect ratio; Scan mode; Pixel to Pixel; Image freeze; Noise reduction; Full Waveform Monitoring; Exposure;</p> <p>HDMI loop-through output; Full Touch Screen; Center Marker; Zoom-in; Image Flip; Monochrome; Peaking Focus; False color; Histogram; Zebra; Customize hot key; Safe Marker</p>	
Power Consumption:	≤9W	
Input Voltage:	DC 7~24V	
Output Voltage:	DC 8V	
Install Way:	1/4-20 thread points	
Operating Temperature:	-20°C~65°C	
Storage Temperature:	-30°C~65°C	
Unit Size:	178*117*22.2 (mm)	



Unit Weight:	380g
Material:	ABS Engineering plastic