



# Clifton Cameras Product Specification

## EcoFlow RIVER 2 Pro UK

### Specifications

|                                |  |
|--------------------------------|--|
| Capacity:                      | 768Wh  |
| Net Weight:                    | Approximately 17.2lbs                                      |
| Dimensions:                    | 270 x 260 x 226mm  |
| AC Input:                      | 100-120V~50Hz/60Hz, 940W Max                               |
| Solar Input:                   | 11-50V 13A, 220W Max                                       |
| USB-C Input/Output:            | 5/9/12/15/20V 5A, 100W Max                                 |
| DC Output:                     | 12.6V, 10A/3A/3A, 126W Max                                 |
| USB-A Output:                  | 5V, 2.4A, 12W Max  |
| AC Output:                     | Pure Sine Wave, 800W total (surge 1600W), 120V ~ 50Hz/60Hz |
| Cell Chemistry:                | LFP  |
| Cycle Life:                    | 80%+ capacity after 3000 cycles                            |
| Discharge Temperature:         | 14°F to 113°F  |
| Charge Temperature:            | 32°F to 113°F  |
| Optimal Operating Temperature: | 68°F to 86°F   |
| Storage Temperature:           | 14°F to 113°F (68°F to 86°F is best)                       |
| Car Input:                     | 12V/24V, 8A, 100W Max                                      |
| DC5521 Output:                 | 12.6V, 3A, 36W Max   |
| App Control:                   | Wi-Fi, Bluetooth   |

1. Using RIVER 2 Pro six times a week, 3000 full 100% cycles will last 9.6 years until it drops to 80%.
2. BMS includes over-voltage, overloading, over-temperature, short circuit, low-temperature, low voltage, and overcurrent.
3. When charging and discharging at high wattage, RIVER 2 Pro may make a noise up to 62db.