

Clifton Cameras Product Specification

GPO Passion ED 10x42 Binoculars

Specifications

Prism type		Schmidt-Pechan
Magnification		10x
Field of view (FOV) at 1.000y		342
Field of view (FOV) at 1.000m		114
Objective diameter (mm)	Effective diameter	42
Ocular diameter (mm)	Effective diameter	23,7
Exit pupil diameter (mm)	Measurement of the pupilary ocular beam	4,2
Eye Relief (inches)	From the last optical surface	0,63
Eye Relief (mm)	From the last optical surface	16
Housing	Main body and hinge	magnesium
Close focus (feet)	Shortest focal distance	6,6
Close focus (meters)	Shortest focal distance	2
Inter pupilary distance (IPD)	Center pupil to center pupil measurement	56 – 75
Dioptric compensation range		-2,5/+2,5
Waterproof	Mbars	100
Waterproof Transmission Daylight	Mbars ISO 14490-5:2005	100 90%
Transmission Daylight	ISO 14490-5:2005	90%
Transmission Daylight Height (inches)	ISO 14490-5:2005 Without covers	90%
Transmission Daylight Height (inches) Height (mm)	ISO 14490-5:2005 Without covers Without covers	90% 2,2 55
Transmission Daylight Height (inches) Height (mm) Weight (ounces)	ISO 14490-5:2005 Without covers Without covers Without covers	90% 2,2 55 25,5
Transmission Daylight Height (inches) Height (mm) Weight (ounces) Weight (grams)	ISO 14490-5:2005 Without covers Without covers Without covers Without covers	90% 2,2 55 25,5 725
Transmission Daylight Height (inches) Height (mm) Weight (ounces) Weight (grams) Lentgh (inches)	ISO 14490-5:2005 Without covers Without covers Without covers Without covers At outside diameter	90% 2,2 55 25,5 725 5,4