

# **Clifton Cameras Product Specification**

## **Hasselblad 907X Anniversary Edition Kit**

#### **Specifications**

#### 907X Anniversary Edition

Camera Type Medium Format Mirrorless Digital camera with Autofocus, Auto exposure and

interchangeable lenses.

Construction Machined aluminium. Tripod socket 1/4".

Sensor Type CMOS, 50 megapixels (8272  $\times$  6200 pixels, 5.3  $\times$  5.3  $\mu$ m).

Sensor Dimensions  $43.8 \times 32.9 \text{ mm}.$ 

Image Size Stills: 3FR RAW capture 106 MB on average. JPEG: Up to 22 MB, TIFF 8 bit: 154 MB.

Video: 2.7K (2720 x 1530) and HD (1920 x 1080), max 29:59 minutes/clip). Video

covers the full sensor width in a 16:9 ratio.

File Format Hasselblad 3FR RAW, Full size JPEG. Video: H.264 Compressed (29,97 fps).

Shooting Mode Single shot and Video, Continuous, Self Timer, Interval Timer, Exposure Bracketing

and Focus Bracketing.

Colour Definition 16-bit; Dynamic range up to 14 stops.

ISO Speed Range ISO Auto, 100, 200, 400, 800, 1600, 3200, 6400, 12800, 25600.

Storage Options Dual UHS-II SD cards or tethered to Mac or PC. Max 1 TB. SD Cards can be used in

Overflow or Backup (images only) mode. It is recommended to use high-speed UHS-II

SD cards.

Colour Management Hasselblad Natural Colour Solution (HNCS).

Storage Capacity A 64 GB card holds approximately 600 RAW or 6000 JPEG High Quality images on

average.

User Interface Touch interface including swipe, scroll and pinch/spread to zoom. Camera grip with

buttons and Scroll Wheels. Many camera functions and settings can be controlled from

a tethered computer or iPad Pro/iPad Air (2019) over Wi-Fi or tethered.

Display 3.2 inch TFT type, 24 bit colour, 2.36 M dots (1024 x 768). Can be tilted up to 90

degrees.

Live View On camera and host computer with high frame rate.

Histogram Feedback Yes, in Browse Mode on rear display.

IR Filter Mounted in front of sensor.

Acoustic Feedback Yes.



Software Phocus for Mac and Windows. Compatible with Adobe Photoshop Lightroom® and

Adobe Camera Raw®.

Phocus Mobile 2 for iPad Pro, iPad Air (2019 or later) and iPhone (iOS 12 or later).

Platform Support Macintosh: OS X version 10.12.2 or later.

PC: XP/Vista/Windows 7 (32 and 64 bit)/8 / 10.

iOS device Support iPad Pro, iPad Air (2019 or later) and iPhone (iOS 12 or later).

Host Connection Type USB 3.0 (5 Gbit/s) Type-C connector.

Additional Connections Audio In/Out.

Operating Temperature -10 to 45 °C. 14 to 113 °F.

Wi-Fi 802.11 b, g, n, a, ac (a and ac depending on region).

Lenses Hasselblad XCD lenses with built in electronically controlled shutter and aperture. Automatic or

manual focusing with instant manual focus override. Lens shades can be mounted in reverse for

transport.

Compatible with all H System lenses and some H System accessories using an XH Lens

Adapter.

Also compatible with V System and XPan Lenses using a XV or XPan Lens Adapter. Many other

lenses via 3rd party lens adapters (E-shutter only).

Shutter Electronically controlled lens shutter with speeds up to 1/2000 s. Flash sync at all

speeds. Optional electronic shutter.

Shutter Speed Range 68 minutes to 1/2000 s with XCD Lenses. 1/800 s or 1/2000 s with HC/HCD Lenses.

Electronic shutter 68 min to 1/10000 s.

Flash Sync Speed Flash can be used at all shutter speeds. Mechanical shutter only.

Flash Compatibility Socket for connection of external flashes via included sync cable.

Focusing Automatic and manual focusing. Instant manual focus override. Automatic focusing

using contrast detection. 100% zoom or Focus Peaking available in manual focus. Up

to 117 selectable autofocus points. Distance scale available in Live View.

Exposure Metering Spot, centre weighted and centre spot.

Power Supply Rechargeable Li-ion battery (7.27 VDC/3400 mAh). Compatible with the 3200 mAh

battery.

Can be charged in camera via USB or with optional external charger. Plug for external

DC Power.

Dimensions CFV II 50C: 91 x 93 x 61 mm

907X: 102 × 91 × 28 mm

907X + CFV II 50C: 102 × 93 × 84 mm

Weight CFV II 50C: 540 g



CFV II 50C + battery: 646 g

907X: 198 g

907X + CFV II 50C + battery: 865 g

XCD 3,5/30: 581 g

### XCD 3,5/30 Lens Anniversary Edition

#### **General Lens Data**

Focal length 31.0 mm

Equivalent Focal length (24x36) 24 mm

Aperture range 3.5 - 32

Angle of view diag/hor/vert 83°/71°/56°

Length/diameter 88 mm/83 mm

Length (from camera lens mount flange) 83 mm

Weight (excl. covers and lens shade) 581 g

Filter diameter 77 mm

Lens Design 11 elements in 10 groups

1 aspherical element

Focus Type Full focusing with floating mechanism

Entrance Pupil Position 75mm in front of image plane

#### **Close Focus Range Data**

Minimum distance object to image plane 0.4 m

Maximum image scale 1:9.6

Corresponding area of coverage 42 x 32 cm

Corresponding exposure reduction 0.3 f-stops

Compatibility Hasselblad X System cameras, Hasselblad 907X series cameras