

Clifton Cameras Product Specification

Leica Summilux-M 35mm f1.4 Classic Steel Rim

Specifications

Lens:	Leica Summilux-M 35 f/1.4
Order Number:	Silver, chrome-plated: 11301
View angle (diagonal/horizontal/vertical)	
Full-frame (24 x 36 mm):	62.5°, 53.6°, 37.2°
For M8 (18 x 27 mm):	49.0°, 41.5°, 28.3°; equivalent focal length approx. 47.5 mm
Lens system	
Number of lenses/assemblies:	7/5
Position of the entrance pupil before the bayonet:	21.2 mm
Focus range:	1 m to infinity
Focusing	
Scale:	Combined scale meter (m)/foot(ft)
Smallest object field:	Full-frame: 631 x 947 mm, M8: 473 x 710 mm
Largest scale:	1:26.3
Aperture	
Setting/Function:	Lock blade, with half-increment lock settings
Smallest aperture:	16
Number of aperture blades	10
Bayonet:	Leica M bayonet with 6-bit encoding
Filter thread:	46
Lens hood:	Included in the scope of delivery: 1x click-on (rectangular) and 1x screw-on E46 (round)
Dimensions	
Length:	Approx. 35 mm/57 mm/52 mm (without lens hood/with rectangular lens hood/with round lens hood)
Diameter:	Approx. 66.5 mm (without lens hood)



Weight:

Approx. 200 g/221 g/214 g (without lens hood/with rectangular lens hood/with round lens hood)